



Model ID330 DI

Iron Construction

Standard Clearance

5 x 4" Std. Port Size



There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.


Created on November 30, 2000

Model ID330 DI


Iron Construction

Standard Clearance



5 x 4" Std. Port Size




Viscosity: 10,000 cst



Viscosity: 100,000 cst



Viscosity: 1,000,000 cst



There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.



Created on November 30, 2000

Model ID330 DI

Iron Construction

Hot Clearance

5 x 4" Std. Port Size



There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.


Created on November 30, 2000

Model ID330 DI


Iron Construction

Hot Clearance



5 x 4" Std. Port Size




Viscosity: 10,000 cst



Viscosity: 100,000 cst



Viscosity: 1,000,000 cst



There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.


Created on November 30, 2000

Model ID330 SS



Stainless Steel Construction

Standard Clearance


5 x 4" Std. Port Size



Viscosity: 100 cst



Viscosity: 1,000 cst



There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.


Created on November 30, 2000

Model ID330 SS



Stainless Steel Construction

Standard Clearance



5 x 4" Std. Port Size




Viscosity: 10,000 cst



Viscosity: 100,000 cst



Viscosity: 1,000,000 cst



There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.



Created on November 30, 2000

Model ID330 SS

Stainless Steel Construction

Hot Clearance

5 x 4" Std. Port Size



There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.




Created on November 30, 2000

Model ID330 SS

Stainless Steel Construction

Hot Clearance

5 x 4" Std. Port Size



There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.

Created on November 30, 2000